



## TRIPLE QX SYNPLUS 5W40 SYNTHETIC

Document version: December 11th 2024



### Description

This TQX SYNPLUS 5W40 synthetic based engine oil is formulated to meet the specifications of different OEMs. It guarantees outstanding engine protection, regardless of operational conditions, by offering low fluidity at cold start and stable viscosity at high temperatures.

### Performance level

ACEA A3/B4  
API SN / CF  
BMW LONGLIFE-01  
Fiat 9.55535-M2  
MB 229.1 / 226.5 / 229.3  
Opel/GM GM-LL-B-025  
Porsche A40  
Renault RN 0710 / RN 0700  
VW 505.00 / 502.00 / 501.01 / 505.01

### Packing units

ART.NO.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
TQX.521776032	1 L	12	450
TQX.521776031	5 L	4	112
TQX.521776035	20 L	1	30
TQX.521776039	60 L	1	12
TQX.521770066	199 L	1	2

## Typicals

TEST	VALUE	
Kinematic Viscosity at 100°C	13.8	mm <sup>2</sup> /s
Kinematic Viscosity at 40°C	78.9	mm <sup>2</sup> /s
Viscosity Index	172	
Density at 15°C	0.854	kg/l
Pourpoint	-39	°C
Total Base Number	10.0	mgKOH/g