



# TRIPLE QX SYNPLUS C3 5W30 SYNTHETIC

Document version: December 11th 2024



## Description

This TQX SYNPLUS C3 5W30 mid-SAPS synthetic lubricant meets the specifications of different OEM-s. The combination of excellent low viscosity properties and highly protective additives enable the engine to run with higher fuel efficiency.

## Performance level

ACEA C3  
API SN / CF  
BMW LL-04&lt;2019  
GM dexos 2  
MB 229.52 / 229.51  
VW 505.01 / 505.00

## Packing units

ART.NO.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
TQX.521776062	1 L	12	-
TQX.521776061	5 L	4	-
TQX.521776065	20 L	1	-
TQX.521776069	60 L	1	12
TQX.521772016	199 L	1	-

## Typicals

TEST	VALUE	
Kinematic Viscosity at 40°C	67.5	mm <sup>2</sup> /s
Kinematic Viscosity at 100°C	11.8	mm <sup>2</sup> /s
Viscosity Index	172	
Flashpoint COC	232	°C
Density at 15°C	0.850	kg/l
Pourpoint	-39	°C
Total Base Number	7.0	mgKOH/g
Sulphated Ash	0.79	mass%