



## TRIPLE QX SYNPLUS PD 5W40 SYNTHETIC

Document version: December 11th 2024



### Description

This TQX SYNPLUS PD 5W40 synthetic lubricant meets the demanding requirements of the VW 505.01 specification in terms of resistance to oxidation, oil thickening and the formation of sludge in the engine. It is a mid SAPS oil providing reliable protection of after-treatment exhaust systems and Diesel Particulate Filters.

### Performance level

ACEA C3  
API SN / CF  
BMW LL-04&lt;2019  
Ford WSS-M2C917-A  
GM dexos 2  
MB 229.51 / 229.31  
Porsche A40  
Renault RN 0710 / RN 0700  
VW 505.01 / 505.00

### Packing units

ART.NO.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
TQX.521776082	1 L	12	-
TQX.521776081	5 L	4	-
TQX.521776085	20 L	1	-
TQX.521776089	60 L	1	12
TQX.521772036	199 L	1	-

## Typicals

TEST	VALUE	
Kinematic Viscosity at 40°C	79.1	mm <sup>2</sup> /s
Kinematic Viscosity at 100°C	13.8	mm <sup>2</sup> /s
Viscosity Index	177	
Density at 15°C	0.849	kg/l
Pourpoint	-39	°C
Total Base Number	6.8	mgKOH/g