



TRIPLE QX ULTRA DIESEL 15W40 MINERAL

Document version: December 11th 2024



Description

TQX ULTRA Diesel 15W40 is a high-performance mineral diesel engine oil formulated to deliver reliable performance in a broad range of heavy-duty applications. It is suitable for low-emission engines (Euro II, Euro III and some Euro IV engines).

Performance level

ACEA A3/B4 / E7
API SL / CI-4
Caterpillar ECF-2 / ECF-1-a
Cummins CES 20078 / CES 20077
Detroit Diesel 93K215
Deutz DQC III-10
Global DHD-1
JASO DH-1
Mack EO-N / EO-M Plus
MAN 3275-1
MB 228.3
MTU Oil Category 2
Renault RLD-2
Volvo VDS-3

Packing units

| ART.NO. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|---------------|--------|----------------|------------------|
| TQX.521776112 | 1 L | 12 | - |
| TQX.521776111 | 5 L | 4 | - |
| TQX.521776115 | 20 L | 1 | - |
| TQX.521772116 | 199 L | 1 | - |

Typicals

| TEST | VALUE | |
|------------------------------|-------|--------------------|
| Kinematic Viscosity at 100°C | 13.6 | mm ² /s |
| Kinematic Viscosity at 40°C | 99.7 | mm ² /s |
| Viscosity Index | 136 | |
| Density at 15°C | 0.883 | kg/l |
| Pourpoint | -32 | °C |
| Total Base Number | 9.2 | mgKOH/g |